


# H01N2-D

## CAVI PER SALDATRICI (ARC WELDING CABLES)

Model Product: 256 - 20230915



Flexible conductor bare or tinned copper, class 6.  
Paper tape.  
Elastomeric mixture Insulation in EM5 quality.

### STANDARDS

CEI EN 50525-2-81 CEI 20-19/6 (CENELEC HD 22.6 S2)  
CEI EN 60332-1-2 (CEI 30-35) BS EN 60332-1-2 NF EN  
60332-1-2 DIN EN 60332-1-2  
EN 60811-404

Accordingly to the standards BT 2014/35/UE- 2011/65/EU (RoHS 3)

### COMMON FEATURES

For portable electrode-carriers use. It's primary to follow the table's data of the user guide CEI 20-40 in merit to the service cycles, the intensities of current and the voltage fall. In order to reduce the effects of the alternating current on the voltage fall, the cables forming the welding circuit must be maintained as close as possible. For use in the automobile industry, in shipbuilding in transport and conveyor, tool marking machinery, welding robots ect.. They are suitable for use in dry and damp conditions. Outdoor use for a limited.

### EMPLOYMENT

Minimum bending radius per D cable diameter (in mm):

6D

During installation, when the cable is pulled, it has not to revolve about its axis

Maximum pulling stress: 50 Nmm<sup>2</sup>

### PACKING

100mt. rings in thermoplastic film or drums to agree.

### CABLES FOR ARC WELDING WITH NORMAL FLEXIBILITY

Nominal voltage U0: 100 V

Nominal voltage U: 100 V

Test voltage: 1000 V

Maximum operating temperature: +85°C

Maximum short circuit temperature: +250°C

Minimum installation and laying temperature: -20°C

Min. operating temperature (without mechanical shocks): -35°C

Minimum installation and laying temperature: -20°C

### CORE COLOURS

Single core: Black ; On request Red

### INK MARKING

GENERAL CAVI - IEMMEQU <HAR> - H01N2-D - year

### NOTE

Characteristics Particular in protected/fixed installation and without mechanical stresses minimum use temperature -40 °C

CEI 20-40 "Guide for the correct use of low voltage cables"

Oil resistant to EN 60811-404

Being black cables are particularly suitable for resistance to UV rays.

The cable also maintains its high flexibility under the effect of ozone, light, oxygen, inert gas, oil or petrol.



H01N2-D

CAVI PER SALDATRICI (ARC WELDING CABLES)

Model Product: 256 - 20230915



Cores number	Cross section	Approx conductor diameter	Insulation medium thickness	External diameter		Approx cable weight	Electric resistance at 20°C red copper	Current carrying capacities 85°C	
				Minimum	maximum			Continuous Load	Intermittent load
(N°)	(mm²)	(mm)	(mm)	(mm)	(mm)	(kg/km)	(Ohm/km)	(A)	(A)
Single core									
1x	10	4.2	2.0	7.7	9.7	148	1.91	100	140
1x	16	5.3	2.0	8.8	11.0	207	1.21	110	160
1x	25	6.2	2.0	10.1	12.7	289	0.780	140	200
1x	35	7.7	2.0	11.4	14.2	380	0.554	180	250
1x	50	9.0	2.2	13.2	16.5	532	0.386	210	320
1x	70	10.7	2.4	15.3	19.2	730	0.272	270	400
1x	95	12.8	2.6	17.1	21.4	955	0.206	330	500
1x	120	15.0	2.8	19.2	24.0	1184	0.161	380	600
1x	150	16.5	3.0	21.1	26.4	1466	0.129	440	700
1x	185	17.9	3.2	23.1	28.9	1760	0.106	480	800
1x	240*	20.1	3.4	25.8	32.1	2010	0.0801	-	-

MINIMUM ORDER QUANTITY  
\*No IMQ <HAR>