

Miele



PDR 507 [EL MAR 3 AC 400-480V 50-60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 7.0 kg.



- Drum volume 130 l, load capacity 7.0kg
- Tested for intensive use – unparalleled Miele quality
- Language-neutral fascia panel with rotary control – M Select
- Precision drying of all fabrics – PerfectDry

EAN: 4002516220053 / Article number : 52507387MAR / Material number: 11300980

Construction type and version	
Construction type	Front-loader, stackable
Range	Performance
Front	Lotos white, enamelled
Maximum load size in kg	7.0
Drum volume in l	130
Drying system	Vented
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Maximum evaporation capacity in l/hour	4.4
Specific energy consumption in kWh/kg	0.50
Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kWh/kg	0.50
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in kWh/kg	0.42
Programme duration in min.	46
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	46
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in minutes	41
Controls	
Control system	M Select
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Control panel with easy-to-understand symbols	•
Language can be selected easily at any time	•
Standard electrical connection	
Heating type	Electrical
Electrical connection	3~ 440V 50/60HZ
Electric heater rating in kW	5.16
Total connected load in kW	5.40
Fuse rating in A	10

PDR 507 [EL MAR 3 AC 400-480V 50-60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 7.0 kg.



Possible voltage variant 1	
Electrical connection	3~ 400V 50/60HZ
Electric heater rating in kW	4.3
Total connected load in kW	4.50
Fuse rating in A	10
Possible voltage variant 2	
Electrical connection	3~ 480V 50/60HZ
Electric heater rating in kW	6.1
Total connected load in kW	6.40
Fuse rating in A	10
Dimensions and weight	
External dimensions, net height in mm	850
External dimensions, net width in mm	596
External dimensions, net depth in mm	717
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	820
Net weight in kg	49
Gross weight in kg	55
Maximum floor loading in N	920
Emissions data	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	0.76
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Communication slot	•
Drying basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•

PDR 507 [EL MAR 3 AC 400-480V 50-60Hz]

Vented dryer, electrically heated

Lloyd's Register approved, load size 7.0 kg.



Standards, test certificates and symbols	
CE	•
Splash-proof safety rating IPX4	•
WEEE	•
Lloyd's Register	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited
Fairacres
Marcham Road
Abingdon
OX14 1TW

Sales: 0845 365 6636
Customer Service: 0845 365 6608
miele-professional@miele.co.uk
www.miele.co.uk/professional
Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment.
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.