

**Miele**



PDR 507 HP [EL MAR 1N AC 230V 60Hz]

Heat-pump dryers

Lloyd's Register approved, load size 7.0 kg.



- Drum volume 130 l, load capacity 7.0kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry

EAN: 4002516246930 / Article number : 52507188MAR / Material number: 11300970

<b>Construction type and version</b>	
Construction type	Front-loader, stackable
Range	Performance
Front	Lotos white, enamelled
Maximum load size in kg	7.0
Drum volume in l	130
Drying system	Heat pump
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for offshore use	•
Suitable for marine use	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	2.7
Specific energy consumption in kWh/kg	0.20
Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kWh/kg	0.20
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in kWh/kg	0.17
Programme duration in min.	67
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	67
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in minutes	57
<b>Controls</b>	
Control system	M Select
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Control panel with easy-to-understand symbols	•
Language can be selected easily at any time	•
<b>Standard electrical connection</b>	
Heating type	Heat pump
Electrical connection	230V~ 60HZ
Total connected load in kW	1.20
Fuse rating in A	10
Provided with plug	•

PDR 507 HP [EL MAR 1N AC 230V 60Hz]

Heat-pump dryers

Lloyd's Register approved, load size 7.0 kg.



<b>Dimensions and weight</b>	
External dimensions, net height in mm	850
External dimensions, net width in mm	596
External dimensions, net depth in mm	777
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	820
Net weight in kg	69
Gross weight in kg	74
Maximum floor loading in N	920
<b>Emissions data</b>	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	3.60
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Fluff filter in the door	•
Low-maintenance heat exchanger filter system	•
PerfectDry	•
SoftLift drum ribs	•
Gentle tumble function	•
Condensed water drainage	•
Communication slot	•
Drying basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	95
Contains fluorinated greenhouse gases	•
Hermetically sealed system	•
Coolant	R134a
Refrigerant quantity in kg	0.59
Refrigerant global warming potential in kg CO <sub>2</sub> e	1,430
Appliance global warming potential in kg CO <sub>2</sub> e	844
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
LAN/WiFi module (optional)	•
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
Lloyd's Register	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited  
Fairacres  
Marcham Road  
Abingdon  
OX14 1TW

Sales: 0845 365 6636  
Customer Service: 0845 365 6608  
[miele-professional@miele.co.uk](mailto:miele-professional@miele.co.uk)  
[www.miele.co.uk/professional](http://www.miele.co.uk/professional)  
Twitter: @MieleProf

**Professional laundry, dishwashing, disinfection and sterilisation equipment.**  
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.