

Miele

The world
of Miele Marine



PRI 421 [SOM EL LAM IB RF]

Rotary ironer, electrically heated

with leaf-spring padding, feed-in belts and return feed for marine applications.

Model and design	
Construction type	Laundry infeed to the front, laundry outfeed to th
Can be set up against a wall	•
Range	Professional
Roller diameter in mm	365
Working width in mm	2040
Heater plate material	Aluminium
Padding	Leaf-spring padding
Ironer cover	ARAMID needle-felt cloth
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Max. ironing performance at 50 % residual moisture in kg/h	67
Tested operating hours	20000
Controls	
Control system	Touch display
Programme setting	Setting defined programme parameters
Minimum ironing speed, controlled in m/min	1.5
Maximum ironing speed, controlled in m/min	5.4
Adjustable temperature	Continuous
Standard electrical connection	
Heating type	Electrical
Electrical connection	3 AC 400V 50-60HZ
Electric heater rating in kW	22.9
Total connected load in kW	23.5
Fuse rating in A	50
Dimensions and weight	
External dimensions, height in mm	1110
External dimensions, width in mm	2759
External dimensions, depth in mm	1441
External dimensions, gross height in mm	1388
External dimensions, gross width in mm	2866
External dimensions, gross depth in mm	1096
Net weight in kg	458
Gross weight in kg	537
Emissions data	
Heat dissipation into the room in MJ/h	13.7

- Capacity atr_c_PP_115510 kg/h, roller diameter 365 mm mm, roller width 2040 mm mm
- Fast cooling of textiles - EasyFold feed table
- State-of-the-art controls – Touch display
- Selection of the most important settings - favourite programmes
- Perfect rotary ironing performance - flexibly positioned heater plate

PRI 421 [SOM EL LAM IB RF]

Rotary ironer, electrically heated

with leaf-spring padding, feed-in belts and return feed for marine applications.

Features	
Patented EasyFold out-feed table	•
Outfeed table extension (optional)	•
HPC heater plate	•
Automatic finger guard	•
FlexControl footswitch	•
In-feed table with feed-in bands	•
Pick-off bands	•
Laundry box	•
Laundry return feed	•
Cover (optional)	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Peak load cut-out/energy management (optional)	•
Test certificate	
VDE	•
CE	•
WEEE	•
VDE-EMC	•
Splash-proof IPX0	•
Complies with Machinery Directive 2006/42/EC	•

Miele

Miele & Cie. KG

Carl-Miele-Straße 29
33332 Gütersloh
Germany
Tel. +49 5241 89-0
www.miele-marine.com

International Service Contacts

Americas: +1 609419 4376
Australia, Asia, Oceania: +61 3 9764 7880
Europe, Africa, Middle East: +049 5241 89 566 877

Email: service@miele-marine.com