

Miele

The world
of Miele Marine



PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, EL heated, with drain pump

Lloyd's Register approved, load capacity 8 kg

Model and design	
Construction type	Front-loader, stackable
Range	Performance Plus
Front	Lotos white, enamelled
Load in kg	8
Drum volume in l	73
Door opening [Ø] in mm	300
Door opening angle in degrees	167
Door hinge	right
Maintenance-free synchronous motor	•
Honeycomb drum with perforated drum rear panel	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Specific water consumption for cold water connection in l/kg	6.4
Specific energy consumption for cold water connection in kWh/kg	0.13
Specific water consumption for hot water connection in l/kg	6
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in l	51
Energy consumption with cold water connection in kW	1.05
Programme duration in minutes with cold water connection	59
Water consumption with hot water connection in l	48
Energy consumption with hot water connection in kW	0.5
Programme duration in minutes with cold water and hot water connection	49
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	45
Spin speed in rpm	1600
g factor	704
Tested operating hours	30000
Controls	
Control system	M Touch Flex
Programmability	programmable
Max. delay start in h	96
Time left display	•
Programme sequence indicator	•
Language can be selected easily at any time	•

- Drum volume 73 l, load capacity 8 kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience w. full-touch colour display –M Touch Flex
- Thorough cleaning with professional wash programmes

PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, EL heated, with drain pump
Lloyd's Register approved, load capacity 8 kg.

Dispensing	
Detergent drawer	3 compartments
CapDosing	•
Flexible dispensing adapter	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•
Standard electrical connection	
Heating type	Electrical
Electrical connection	2N~ 400V 50-60 HZ
Heater rating in kW	5.3
Total connected load in kW	5.5
Fuse rating in A	16
Possible voltage variant 1	
Electrical connection	230V~
Heater rating in kW	2.65
Total connected load in kW	2.85
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Drain pump	DN 22
Dimensions and weight	
External dimensions, height in mm	850
External dimensions, width in mm	596
External dimensions, depth in mm	714
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	768
Net weight in kg	104
Gross weight in kg	108
Emissions data	
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1

PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, EL heated, with drain pump
Lloyd's Register approved, load capacity 8 kg.

Features	
3-dimensional imbalance monitoring	•
Commercial shock absorbers	•
Hard-wearing stainless-steel flange	•
Disinfection rinse	•
EcoSpeed	•
Pre-ironing	•
Efficient drum rib technology	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Flow meter	•
LED drum lighting, class 1	•
Communication slot	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
Test certificate	
WEEE	•
Lloyd's Register	•
Complies with Machinery Directive 2006/42/EC	•

PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, EL heated, with drain pump
Lloyd's Register approved, load capacity 8 kg.

Model and design	
Construction type	Front-loader, stackable
Range	Performance Plus
Front	Lotos white, enamelled
Load in kg	8
Drum volume in l	73
Door opening [Ø] in mm	300
Door opening angle in degrees	167
Door hinge	right
Maintenance-free synchronous motor	•
Honeycomb drum with perforated drum rear panel	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Specific water consumption for cold water connection in l/kg	6.4
Specific energy consumption for cold water connection in kWh/kg	0.13
Specific water consumption for hot water connection in l/kg	6
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in l	51
Energy consumption with cold water connection in kW	1.05
Programme duration in minutes with cold water connection	59
Water consumption with hot water connection in l	48
Energy consumption with hot water connection in kW	0.5
Programme duration in minutes with cold water and hot water connection	49
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	45
Spin speed in rpm	1600
g factor	704
Tested operating hours	30000
Controls	
Control system	M Touch Flex
Programmability	programmable
Max. delay start in h	96
Time left display	•
Programme sequence indicator	•
Language can be selected easily at any time	•

- Drum volume 73 l, load capacity 8 kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience w. full-touch colour display –M Touch Flex
- Thorough cleaning with professional wash programmes

PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, EL heated, with drain pump
Lloyd's Register approved, load capacity 8 kg.

Dispensing	
Detergent drawer	3 compartments
CapDosing	•
Flexible dispensing adapter	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•
Standard electrical connection	
Heating type	Electrical
Electrical connection	2N~ 400V 50-60 HZ
Heater rating in kW	5.3
Total connected load in kW	5.5
Fuse rating in A	16
Possible voltage variant 1	
Electrical connection	230V~
Heater rating in kW	2.65
Total connected load in kW	2.85
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Drain pump	DN 22
Dimensions and weight	
External dimensions, height in mm	850
External dimensions, width in mm	596
External dimensions, depth in mm	714
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	768
Net weight in kg	104
Gross weight in kg	108
Emissions data	
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1

PWM 908 [EL DP MAR 2 NAC 400V 50-60Hz]

Professional washing machine, Little Giants, EL heated, with drain pump
Lloyd's Register approved, load capacity 8 kg.

Features	
3-dimensional imbalance monitoring	•
Commercial shock absorbers	•
Hard-wearing stainless-steel flange	•
Disinfection rinse	•
EcoSpeed	•
Pre-ironing	•
Efficient drum rib technology	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Flow meter	•
LED drum lighting, class 1	•
Communication slot	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
Test certificate	
WEEE	•
Lloyd's Register	•
Complies with Machinery Directive 2006/42/EC	•

Miele

Miele & Cie. KG

Carl-Miele-Straße 29
33332 Gütersloh
Germany
Tel. +49 5241 89-0
www.miele-marine.com

International Service Contacts

Americas: +1 609419 4376
Australia, Asia, Oceania: +61 3 9764 7880
Europe, Africa, Middle East: +049 5241 89 566 877

Email: service@miele-marine.com