

## PP-V14-PCB-THR-RJ45-8P-J-M-ANG-SHLD



Part number	09 35 002 2101
Specification	PP-V14-PCB-THR-RJ45-8P-J-M-ANG-SHLD
HARTING eCatalogue	<a href="https://b2b.harting.com/09350022101">https://b2b.harting.com/09350022101</a>
Features	Intuitive locking mechanism

### Identification

Category	Connector
Series	Han <sup>®</sup> PushPull
Identification	RJ45
Element	Female
Specification	Angled

### Version

Termination method	Solder termination
--------------------	--------------------

### Technical characteristics

Rated current	1.75 A
Rated voltage	50 V
Limiting temperature	-40 ... +85 °C
Mating cycles	≥750

### Material properties

Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

### Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14) IEC 60603-7 Mating face
----------------	---



Pushing Performance

## Specifications and approvals

PROFINET	Yes
----------	-----

## Commercial data

Packaging size	360
Net weight	5.18 g
Country of origin	Japan
European customs tariff number	85389099