

# Han HvE Base Surface LC 2 Levers 2 Entri



Part number	19 34 010 0271	
Specification	Han HvE Base Surface LC 2 Levers 2 Entri	
HARTING eCatalogue	https://b2b.harting.com/19340100271	
Identification		
Category	Hoods/Housings	
Series of hoods/housings Han Hv $E^{^{(\!\!R\!)}}$		
Type of hood/housing	Surface mounted housing	

### Version

Locking type	Double locking lever
Han-Easy Lock <sup>®</sup>	Yes
Size	24 B
Version	Side entry
Cable entry	2x M25
Field of application	Special hoods/housings for Han Hv $E^{f \otimes}$ screw terminal

## **Technical characteristics**

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

## Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR
Material (locking)	Polycarbonate Stainless steel
Colour (locking)	RAL 7037 (dust grey)

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



### Material properties

Material flammability class acc. to UL 94 (locking levers)	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
Specifications and approvals	
Approvals	DNV GL
Commercial data	
Packaging size	1
Net weight	323.4 g
Country of origin	Germany
European customs tariff number	85389099