

## Wall mounting socket outlet - with external fixing



| Product description       |                             |
|---------------------------|-----------------------------|
| BALS-Prd.-Nr              | 11765                       |
| EAN                       | 4024941117654               |
| Product category          | Wall mounting socket outlet |
| Current                   | 16A                         |
| Number of poles           | 3p                          |
| Arrangement of phases     | 2P+PE                       |
| Position of earth contact | 6 h                         |
| Voltage                   | 200 - 250V~                 |
| Frequency                 | 50/60Hz                     |

| Product description    |   |
|------------------------|---|
| Protection degree      | IP44  |
| Colour code            | blue RAL 5015   |
| Colour of appliance    | Collar blue RAL 5015, Hinged lid blue RAL 5015, Housing bottom grey RAL 7035, Housing top grey RAL 7035 |
| Connection design      | with screw terminal   |
| Maximum conductor size | 4,0 qmm   |
| Cable entry            | top entry M20   |
| Height                 | 130mm   |
| Width                  | 72mm  |
| Depth                  | 86mm  |
| Dimension of enclosure | 90x72 mm (HxW)  |
| Material of enclosure  | Polyamide   |
| Contacts               | the contact carrier is made of polyamide, the contacts are brass  |

| Additional technical properties |   |
|---------------------------------|---|
|                                 | The cable entry is one at top open and one at bottom closed |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.175 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941117654 |
| Length         | 86 mm         |
| Width          | 72 mm         |
| Height         | 130 mm        |
| Weight         | 0.176 kg      |
| Volume         | 804.96 ccm    |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941827980 |
| Length         | 245 mm        |
| Width          | 177 mm        |
| Height         | 185 mm        |
| Weight         | 1.883 kg      |
| Volume         | 7,140 ccm     |



| Ampere Polzahl             | 16<br>3 | 16<br>4 | 16<br>5 | 32<br>3 | 32<br>4 | 32<br>5 |
|----------------------------|---------|---------|---------|---------|---------|---------|
| a                          | 59,5    | 72,4    | 72,4    | 79,1    | 79,1    | 79,1    |
| b                          | 90,0    | 90,0    | 90,0    | 92,0    | 92,0    | 92,0    |
| c                          | 130,0   | 130,0   | 131,0   | 142,0   | 142,0   | 142,0   |
| d                          | 85,0    | 96,0    | 98,0    | 103,0   | 103,0   | 106,0   |
| e                          | 62,0    | 77,0    | 77,0    | 84,0    | 84,0    | 84,0    |
| f                          | 33,5    | 33,5    | 33,5    | 30,0    | 30,0    | 30,0    |
| h                          | 9,0     | 9,0     | 9,0     | 9,0     | 9,0     | 9,0     |
| i                          | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     |
| k                          | 8,0     | 9,0     | 9,0     | 9,0     | 9,0     | 9,0     |
| l ø                        | 21,0    | 21,0    | 21,0    | 21,0    | 21,0    | 21,0    |
| m                          | 72,0    | 87,0    | 87,0    | 94,0    | 94,0    | 94,0    |
| n                          | M20     | M25     | M25     | M25     | M25     | M25     |
| Leiter mm <sup>2</sup> min | 1,5     | 1,5     | 1,5     | 2,5     | 2,5     | 2,5     |
| Leiter mm <sup>2</sup> max | 4       | 4       | 4       | 10      | 10      | 10      |

1 MB 19