

## Panel mounting socket outlet straight - flange 62x62 fixing centers 47x47




| Product description       |                                                      |
|---------------------------|------------------------------------------------------|
| BALS-Prd.-Nr              | 13669                                                |
| EAN                       | 4024941136693                                        |
| Product category          | Panel mounting socket outlet QUICK-CONNECT, straight |
| Current                   | 16A                                                  |
| Number of poles           | 3p                                                   |
| Arrangement of phases     | 2P+PE                                                |
| Position of earth contact | 9 h                                                  |
| Voltage                   | 380 - 415V~                                          |

| Product description            |                                                                  |
|--------------------------------|------------------------------------------------------------------|
| Frequency                      | 50/60Hz                                                          |
| Protection degree              | IP44                                                             |
| Colour code                    | red RAL 3000                                                     |
| Colour of appliance            | Hinged lid red RAL 3000, Enclosure grey RAL 7035                 |
| Connection design              | screwless spring terminals with KONTEX-contact                   |
| Maximum conductor size         | 4,0 qmm                                                          |
| Cable entry                    | other                                                            |
| Height                         | 70mm                                                             |
| Width                          | 62mm                                                             |
| Depth                          | 86mm                                                             |
| Flange size vertical in mm     | 62mm                                                             |
| Flange size horizontal in mm   | 62mm                                                             |
| Drill hole dist. vertical mm   | 47mm                                                             |
| Drill hole dist. horizontal mm | 47mm                                                             |
| Material of enclosure          | Polyamide                                                        |
| Contacts                       | the contact carrier is made of polyamide, the contacts are brass |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.095 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941136693 |
| Length         | 86 mm         |
| Width          | 62 mm         |
| Height         | 70 mm         |
| Weight         | 0.096 kg      |
| Volume         | 373.24 ccm    |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941828994 |
| Length         | 248 mm        |
| Width          | 158 mm        |
| Height         | 123 mm        |
| Weight         | 1.047 kg      |
| Volume         | 3,960 ccm     |



| Ampere         | 16   | 16   | 16   |  |  |  |  |
|----------------|------|------|------|--|--|--|--|
| Polzahl        | 3    | 4    | 5    |  |  |  |  |
| a              | 62,0 | 72,0 | 72,0 |  |  |  |  |
| b              | 62,0 | 65,0 | 65,0 |  |  |  |  |
| c              | 47,0 | 52,0 | 52,0 |  |  |  |  |
| d              | 47,0 | 52,0 | 52,0 |  |  |  |  |
| e ø            | 5,5  | 5,5  | 5,5  |  |  |  |  |
| f              | 7,0  | 7,0  | 7,0  |  |  |  |  |
| h              | 35,5 | 35,5 | 35,5 |  |  |  |  |
| i              | 51,0 | 53,0 | 53,0 |  |  |  |  |
| k              | 70,0 | 80,0 | 85,0 |  |  |  |  |
| l ø            | 45,0 | 45,0 | 55,0 |  |  |  |  |
| m              | 10,0 | 9,0  | 13,0 |  |  |  |  |
| Leiter mm² min | 1,5  | 1,5  | 1,5  |  |  |  |  |
| Leiter mm² max | 4    | 4    | 4    |  |  |  |  |