




LED ceiling surface-mounted luminaire SUNNY
Artikel-Nr. 12208073



LED ceiling surface-mounted luminaire SUNNY, white, round. Surface mounting, Ceiling-mounted. Direct and indirect light emission, dimmable via trailing-edge phase. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 30W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.700lm, Beam angle: 110°, Adjustability: Not adjustable, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	12208073
Stand:	25.10.2021 22:37
Colour temperature	3000 K / 4000 K / 6000 K
Colour	White
Beam angle	110 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Steel / Plastic
Power	30 W
Lamp	LED
scope of delivery	Including a converter for connection to 230-V mains voltage, dimmable and switch for setting the color temperature to 3000 K, 4000 K or 6000 K. Optional accessories: Color ring set for the indirect component in the colors red, amber and blue.
Colour rendering	CRI > 80
Control	Trailing-edge phase
Outer diameter	330 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Adjustability	Not adjustable
Aufbauhöhe	45 mm
Circuit type	Parallel conduction