



LED surface-mounted / recessed downlight MOON
Artikel-Nr. 12164153



LED surface-mounted / recessed downlight MOON, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Lamps optimized for installation in furniture and wood-based materials. This lamp can be used as a recessed (hole cut-out: 56 mm, installation depth: 3.5 mm, mounting height: 2.2 mm), as well as surface-mounted lamp (total height: 5.9 mm) using the supplied mounting housing. Outer edge nickel matte, magnetically attached cover in the color as per the table of products. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V , Power: 2.6W, Amount of light sources / fittings: 1 Qty, Luminous flux: 180lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 120°, Adjustability: Not adjustable, With control gear: No, control: Dimming depending on driver.

Artikel-Nr.	12164153
Stand:	20.07.2021 18:01

Colour of light	3000 K	control	Dimming depending on driver
Colour	Nickel	Outer diameter	75 mm
Beam angle	120 °	Built-in diameter	56 mm
Amount of light sources / fittings	1 Qty	Installation depth	3.5 mm
Material	Aluminium / Steel / Plastic	Voltage	12V
Power	2,6 W	Degree of protection	IP20
Lamp	LED	Protection class	III
Shipping	Including 2,000 mm connecting cable	Adjustability	Not adjustable
Colour rendering	CRI > 85	Height	5.9 mm
		Circuit type	Parallel conduction