

Han 3A-AK (Kunstst. sw)



| | |
|--------------------|---|
| Part number | 09 20 003 5450 |
| Specification | Han 3A-AK (Kunstst. sw) |
| HARTING eCatalogue | https://b2b.harting.com/09200035450 |

Identification

| | |
|-----------------------------|--|
| Category | Hoods/Housings |
| Series of hoods/housings | Han A® |
| Type of hood/housing | Protection cover |
| Description of hood/housing | for bulkhead mounted housings for surface mounted housings Thermoplastic With fixing cord |

Version

| | |
|----------------------|---|
| Locking type | Single locking lever |
| Size | 3 A |
| Field of application | Standard Hoods/housings for industrial applications |
| Details | for mounted male insert |

Technical characteristics

| | |
|--|---|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP44 IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| | |
|---|----------------------|
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |



Pushing Performance

Material properties

| | |
|-----------------------|----|
| REACH SVHC substances | No |
|-----------------------|----|

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 10 |
| Net weight | 5.68 g |
| Country of origin | Romania |
| European customs tariff number | 85389099 |