

Han M23 P 5+PE Female -C



Part number	09 15 606 3101
Specification	Han M23 P 5+PE Female -C
HARTING eCatalogue	https://b2b.harting.com/09156063101

Identification

Category	Inserts
Series	Han [®] M23 Power
Element	Inserts

Version

Termination method	Crimp termination
Gender	Female
Number of contacts	5
PE contact	Yes
Details	Please order crimp contacts separately. 6x 2 mm

Technical characteristics

Conductor cross-section	0.14 ... 4 mm ²
Rated current	28 A
Rated voltage	600 V
Rated impulse voltage	4 kV
Pollution degree	3
Insulation resistance	>10 ¹³ Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500
Test voltage U _{r.m.s.}	4 kV

Material properties

Material (insert)	Polyamide
Colour (insert)	Blue
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant



Pushing Performance

Material properties

China RoHS e

REACH Annex XVII substances No

REACH ANNEX XIV substances No

REACH SVHC substances No

Specifications and approvals

UL / CSA UL 1977 ECBT2.E235076

Commercial data

Packaging size 5

Net weight 9.1 g

Country of origin Germany

European customs tariff number 85366990