

Han M23 12 Female-C CCW

| Part number | 09 15 112 3111 |
|--------------------|-------------------------------------|
| Specification | Han M23 12 Female-C CCW |
| HARTING eCatalogue | https://b2b.harting.com/09151123111 |
| Identification | |
| Category | Inserts |
| Series | Han [®] M23 Signal |
| Element | Inserts |
| Specification | Marking in opposite direction |

Version

| Termination method | Crimp termination |
|--------------------|--|
| Gender | Female |
| Number of contacts | 12 |
| Details | Please order crimp contacts separately. 12x 1 mm |

Technical characteristics

| Conductor cross-section | 0.08 1.5 mm² |
|-------------------------|---------------------|
| Rated current | 8 A |
| Rated voltage | 200 V |
| Rated impulse voltage | 2.5 kV |
| Pollution degree | 3 |
| Insulation resistance | >10 ¹⁰ Ω |
| Limiting temperature | -40 +125 °C |
| Mating cycles | ≥500 |

Material properties

| Material (insert) | Polyamide |
|---|-----------|
| Colour (insert) | White |
| Material flammability class acc. to UL 94 | V-0 |



Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E235076 |
|----------|-----------------------|
| | |

Commercial data

| Packaging size | 5 |
|--------------------------------|----------|
| Net weight | 4.7 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |