



### Surface-mounted device with attachment via an elongated hole

|                                            |                                                                      |
|--------------------------------------------|----------------------------------------------------------------------|
| <b>Product-Nr.</b>                         | 210700-06                                                            |
| <b>EAN:</b>                                | 4260556626949                                                        |
| <b>Model:</b>                              | LED2WORK DIMMbox                                                     |
| Order number:                              | 210700-06                                                            |
| <b>Model:</b>                              | LED2WORK DIMMbox                                                     |
| <b>Type:</b>                               | Surface-mounted device with attachment via an elongated hole         |
| <b>Power:</b>                              | max. 96 W                                                            |
| <b>Through voltage :</b>                   | 24V DC                                                               |
| <b>Current load max.:</b>                  | 4000 mA                                                              |
| <b>Assignment of PIN 1 input / output:</b> | 24V DC / -                                                           |
| <b>Assignment of PIN 2 input / output:</b> | - / -                                                                |
| <b>Assignment of PIN 3 input / output:</b> | GND / DIM-                                                           |
| <b>Assignment of PIN 4 input / output:</b> | 24V DC / DIM+                                                        |
| <b>Material:</b>                           | Casing: ABS                                                          |
| <b>Output voltage:</b>                     | 24V DC                                                               |
| <b>Dimming:</b>                            | Using a rotary potentiometer                                         |
| <b>INPUT/OUTPUT:</b>                       | M12 pistikupesa koos 3 m (~9,84 ft.) kaabliga / M12 pistik A-koodiga |
| <b>ON/OFF switch:</b>                      | Yes                                                                  |
| <b>Voltage range:</b>                      | 24V DC                                                               |
| <b>Power supply:</b>                       | External                                                             |
| <b>Degree of protection:</b>               | IP54                                                                 |
| <b>Class of protection:</b>                | III                                                                  |
| <b>Operating temperature:</b>              | -20 °C - +50 °C (-4 °F - 122 °F)                                     |
| <b>Storage temperature:</b>                | -20 °C - +80 °C (-4 °F - 176 °F)                                     |
| <b>Dimensions (mm):</b>                    | 122 mm x 38 mm x 45 mm (~4,8" x ~1,5" x ~1,77")                      |
| <b>Weight (net):</b>                       | 450 g (~16 oz)                                                       |
| <b>Gross weight:</b>                       | 500 g (~18 oz)                                                       |
| <b>Markings:</b>                           | CE, UKCA                                                             |
| <b>Feature:</b>                            | Universal DIMMbox for all LED2WORK 24V DC luminaires, except for RGB |