

Han 16B-HBM double lever black



| | |
|--------------------|---|
| Part number | 09 30 716 0301 |
| Specification | Han 16B-HBM double lever black |
| HARTING eCatalogue | https://b2b.harting.com/09307160301 |

Identification

| | |
|-----------------------------|---------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] B |
| Type of hood/housing | Bulkhead mounted housings |
| Description of hood/housing | Black |
| Type | Low construction |

Version

| | |
|----------------------------|---|
| Locking type | Double locking lever |
| Han-Easy Lock [®] | Yes |
| Size | 16 B |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| | |
|--|----------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate |
| | Stainless steel |
| Colour (locking) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |



Pushing Performance

Material properties

| | |
|-----------------------------|-----------|
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 1 |
| Net weight | 120.4 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |