




Schrumpfschlauch mit Innenkleber 3:1, 75/22 mm



4 046725 399391

Leistungsmerkmale

Der mittelwandige RED Schrumpfschlauch mit Kleberbeschichtung wird in 1-Meter-Stangen geliefert.

Folgende Eigenschaften zeichnen den Schrumpfschlauch aus:

- schützt sehr gut gegen Umwelteinflüsse
- besitzt gute elektrische und mechanische Eigenschaften und ist ideal für Niederspannungs-Anwendungen
- UV-beständig und halogenfrei

Technische Daten

- Lagerung: -10 °C bis +40 °C, rel. Luftfeuchtigkeit: <75 %
- Haltbarkeit: 24 Monate
- Mindesttemperatur zur vollständigen Schrumpfung: +120 °C
- Längsschrumpfung 0 ± 10 % max.

Hinweis: Aufgrund der Brandgefahr darf das Schrumpfen nicht unter offener Flamme ausgeführt werden.

DEHA-Nummer

6163796

Artikelnummer

2230-10-0015

EAN

4046725399391

Kennzeichnung

Schrumpfschlauch mit Innenkleber 3:1, 75/22 mm

Allgemeine Daten

Merkmale	
Typ	Warm Schrumpf
Ausführung	mittelwandig
Schrumpfrate	3:1
Innendurchmesser vor Schrumpf	75 mm
Innendurchmesser nach Schrumpf	22 mm
Wandstärke nach Schrumpf	3 mm
Länge	1 m
Betriebstemperatur	-55 - 110 °C
Farbe	schwarz
Werkstoff	Polyolefine (PO-X)
Halogenfrei	ja
Mit Innenkleber	ja
Bedruckbar	ja


Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
6163796	SMK 75.0-22.0	2230-10-0015	4046725399391	5 Stück



Shrink tubing with inner adhesive 3:1, 75/22 mm

**Performance features**

RED medium wall adhesive lined heat shrink tubing is supplied in 1 meter lengths.

The shrink tubing is characterized by the following properties:

- protects very well against environmental influences
- has good electrical and mechanical properties and is ideal for low voltage applications
- UV-resistant and halogen free

Technical specifications

- Storage: -10 °C to +40 °C, rel. Humidity: <75%
- Shelf life: 24 months
- Minimum temperature for full shrinkage: +120 °C
- Longitudinal shrinkage $0 \pm 10\%$ max.

Note: Due to the risk of fire, shrinking must not be performed under an open flame.

DEHA number

6163796

Item number

2230-10-0015

EAN

4046725399391

label

Shrink tubing with inner adhesive 3:1, 75/22 mm

General Data

Features	
Type	Heat-shrink
Model	Medium-walled
Shrink rate	3:1
Inner diameter before heat-shrink	75 mm
Inner diameter after heat-shrink	22 mm
Wall thickness after shrinking	3 mm
Length	1 m
Operation temperature	-55 - 110 °C
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	yes
With inner glue	yes
Printable	yes

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
6163796	SMK 75.0-22.0	2230-10-0015	4046725399391	5 Piece