

# SCT(LED) 200 Trimless



- SCT(LED) 200 Trimless Einbaustrahler sind nur für den Innenbereich zugelassen. Beachten Sie bei der Montage die jeweils gültigen nationalen Unfall- und Verhütungsvorschriften.
- 230 V / 50 Hz Netzanschluss muss bauseitig gemäß der geforderten Schutzart und Schutzklasse vorhanden sein. Schutzart: IP20
- ⚠ 230 V / 50 Hz. Netzanschluss darf nur von Elektrofachkräften durchgeführt werden. Örtliche Vorschriften beachten.**
- Anschlussleitungen nicht über Leuchte führen.
- Leuchte nicht mit Wärmedämm-Material abdecken.
- Leuchtmittel nur bei netzseitig abgeschalteter Leuchte einsetzen oder auswechseln. Leuchtmittelhinweise beachten.
- SCT(LED) 200 trimless recessed spotlights are only useable for indoor areas. When mounting consider the relevant national accident and prevention regulations.*
- 230 V / 50 Hz mains connection must be provided on-site according the required protection type and class. Protection type: IP20*
- ⚠ 230 V / 50 Hz. Mains Connection must only be done by electricans. Consider local regulations.**
- Don't lead the connecting lines across the luminaire.*
- Don't cover luminaire with warmth insulation material.*
- Change or insert lamps only when the luminaire is switched off mains-sided. Consider the references for lamps.*

Type type	Leuchtmittel / Fassung lamp / socket	Einbautiefe ET recess depth [mm]	Deckenausschnitt DA cut-out [mm]	Deckenstärke ceiling thickness [mm]
SCT 201.100	1 x QR111 / G53	120	156 x 156	12.5 - 26.5
SCT 202.100	2 x QR111 / G53	120	285 x 156	12.5 - 26.5
SCT 203.100	3 x QR111 / G53	120	413 x 156	12.5 - 26.5
SCTLED 201.1110	1 x LED AR111 / GU10	155	156 x 156	12.5 - 26.5
SCTLED 202.1110	2 x LED AR111 / GU10	155	285 x 156	12.5 - 26.5
SCTLED 203.1110	3 x LED AR111 / GU10	155	413 x 156	12.5 - 26.5

