

8150/5-V37-306-51-0010-K Art. No. 214174



- Can be used with conventional drives and drives controlled by frequency converters
- Intelligent design: A single rotary actuator for actuating both main and auxiliary contacts, ≥ 20 ms leading auxiliary contact for safely disconnecting the frequency converter
- Version complies with IEC/EN 62626-1, Class 1
- The rotary actuator can be locked with 3 padlocks in the 0-position

WebCode **8150F**



R. STAHL's 8150/5-V37 series safety switches safely disconnect the power supply to machinery and system components for cleaning and repair as prescribed. They can be used at frequencies from 5 to 400 Hz. All of the installed load disconnect switches have an AC-3 switching capacity. The switches can be locked in the 0-position using padlocks.

Technical Data

Explosion Protection

Application range (zones)	1 2 21 22
IECEX gas certificate	IECEX PTB 09.0049
IECEX gas explosion protection	Ex db eb IIC T6 Gb
IECEX dust certificate	IECEX PTB 09.0049
IECEX dust explosion protection	Ex tb IIIC T80 °C Db
ATEX gas certificate	PTB 09 ATEX 1109
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T6 Gb
ATEX dust certificate	PTB 09 ATEX 1109
ATEX dust explosion protection	Ex II 2 D Ex tb IIIC T80 °C Db
Certificates	ATEX (PTB), IECEX (PTB)

Electrical Data

Rated operational voltage AC	690 V / 500 V
Rated operational current	63 A / 80 A
Rated operational current	63 A (T6) 80 A ()
Rated operational current	0 A / 63 A
Switching capacity AC-3 230 V	18.5 – 22 kW
Switching capacity AC-3 400 V	30 – 45 kW
Switching capacity AC-3 440 V	37 – 45 kW
Switching capacity AC-3 500 V	37 – 55 kW
Switching capacity AC-3 690 V	55 – -- kW
Auxiliary contact NC	1 NC
Auxiliary contact NO	1 NO / delayed
Frequency range	50 – 60 Hz

8150/5-V37-306-51-0010-K Art. No. 214174

Ambient Conditions

Ambient temperature	-40 °C ... +42 °C -40 °C ... +40 °C
Extended ambient temperature min.	-40 °C
Extended ambient temperature max.	+57 °C
Extended ambient temperature	-40 ... +57 °C


Mechanical Data

Degree of protection (IP)	IP66
Degree of protection note	acc. to EN/IEC 60529
Enclosure material	1.4404 stainless steel, (AISI 316L), brush finished
Additional terminal	Standard (without)
Connection terminals of auxiliary contact finely stranded max.	2.5 mm ²
Connection terminals of auxiliary contact min.	0.75 mm ²
Conductor cross-section min.	25 mm ²
Conductor cross-section min. 2	35 mm ²
Conductor cross-section max.	50 mm ²
Cable gland	2 x M50 Ø 16 ... 35 mm 1 x M20 Ø 4 ... 13 mm
Type of connection cable	Solid Finely stranded
Construction type	Standard
Dimension A	360 mm
Dimension B	360 mm
Dimension C	196 mm
Colour of handle	Black shroud and handle
Seal	Silicone, foamed
Lockable in	3x in 0
Detailed number of poles	3-pole
Weight	12.6 kg
Weight	27.78 lb

Components

Entry type	Standard 8161, moulded material
------------	---------------------------------

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.