

Han 10B-HMC-gs-R-M25



Part number	19 30 210 1541
Specification	Han 10B-HMC-gs-R-M25
HARTING eCatalogue	https://b2b.harting.com/19302101541

Identification

Category	Hoods/Housings
Series of hoods/housings Han® HMC	
Type of hood/housing	Hoods
Туре	Low construction

Version

Locking type	Single locking lever
Size	10 B
Version	Side entry
Cable entry	1x M25
Field of application	Special hoods and housings for high mating cycles

Technical characteristics

Limiting temperature	-40 +125 °C
Mating cycles with other HMC components	≥10,000
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No



Material properties

|--|

Specifications and approvals

Approvals	DNV GL	
-----------	--------	--

Commercial data

Packaging size	1
Net weight	150.7 g
Country of origin	Germany
European customs tariff number	85389099