

Han 16B-gg-ZV-M32



| Part number | 19 30 016 0487 |
|---|-------------------------------------|
| Specification | Han 16B-gg-ZV-M32 |
| HARTING eCatalogue | https://b2b.harting.com/19300160487 |
| | |
| Identification | |
| Category | Hoods/Housings |
| Series of hoods/housings Han [®] B | |
| Type of hood/housing | Hoods |
| Туре | High construction |

Version

REACH Annex XVII substances

REACH ANNEX XIV substances

| Locking type | Central locking lever (on the hood) |
|--|---|
| Size | 16 B |
| Version | Top entry |
| Cable entry | 1x M32 |
| Field of application | Standard hoods/housings for industrial connectors |
| | |
| Technical characteristics | |
| Limiting temperature | -40 +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |
| Material properties | |
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (locking) | Stainless steel |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

No

No



| Material properties | |
|------------------------------|------------|
| REACH SVHC substances | No |
| | |
| Specifications and approvals | |
| Approvals | DNV GL |
| | |
| Commercial data | |
| | |
| Packaging size | 1 |
| | 1 390 g |
| Packaging size | |