

Han 16B SM Base HC 1xM32 black



| Part number | 19 30 716 0232 |
|--------------------|-------------------------------------|
| Specification | Han 16B SM Base HC 1xM32 black |
| HARTING eCatalogue | https://b2b.harting.com/19307160232 |

Identification

| Category | Hoods/Housings |
|---------------------------------|-------------------------|
| Series of hoods/housings Han® B | |
| Type of hood/housing | Surface mounted housing |
| Description of hood/ housing | Black |
| Туре | High construction |

Version

| Locking type | Double locking lever |
|----------------------------|---|
| Han-Easy Lock [®] | Yes |
| Size | 16 B |
| Version | Side entry |
| Cable entry | 1x M32 |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|-------------|
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-------------------------|----------------------------------|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |



Material properties

| Material flammability class acc. to UL 94 (locking levers) | V-0 |
|--|-----------|
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| Approvals DNV GL |
|------------------|
|------------------|

Commercial data

| Packaging size | 1 |
|--------------------------------|----------|
| Net weight | 414.2 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |