

panel mounting socket outlet, angled - flange 85x85,  
fixing centers 70x70




| Product description       |                                                    |
|---------------------------|----------------------------------------------------|
| BALS-Prd.-Nr              | 12766                                              |
| EAN                       | 4024941127660                                      |
| Product category          | Panel mounting socket outlet Quick-Connect, angled |
| Current                   | 32A                                                |
| Number of poles           | 5p                                                 |
| Arrangement of phases     | 3p+N+PE                                            |
| Position of earth contact | 4 h                                                |
| Voltage                   | 57/100 - 75/130V~                                  |

| Product description            |                                                                  |
|--------------------------------|------------------------------------------------------------------|
| Frequency                      | 50/60Hz                                                          |
| Protection degree              | IP44                                                             |
| Colour code                    | yellow RAL 1012                                                  |
| Colour of appliance            | Hinged lid yellow RAL 1012, Enclosure grey RAL 7035              |
| Connection design              | screwless spring terminals with Kontex-Kontakt                   |
| Maximum conductor size         | 10,0 qmm                                                         |
| Cable entry                    | other                                                            |
| Height                         | 102mm                                                            |
| Width                          | 85mm                                                             |
| Depth                          | 119mm                                                            |
| Flange size vertical in mm     | 85mm                                                             |
| Flange size horizontal in mm   | 85mm                                                             |
| Drill hole dist. vertical mm   | 70mm                                                             |
| Drill hole dist. horizontal mm | 70mm                                                             |
| Material of enclosure          | Polyamide                                                        |
| Contacts                       | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical properties |                        |
|---------------------------------|------------------------|
|                                 | The inclination is 20° |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.235 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941127660    |
| Length         | 119 mm           |
| Width          | 85 mm            |
| Height         | 102 mm           |
| Weight         | 0.236 kg         |
| Volume         | 1,190.135 ccm    |
| Packaging      | Carton           |
| Content amount | 10 ST            |
| EAN            | 4024941829427    |
| Length         | 258 mm           |
| Width          | 183 mm           |
| Height         | 212 mm           |
| Weight         | 2.499 kg         |
| Volume         | 8,750 ccm        |



| Ampere         | 16   | 16   | 16   | 32   | 32   | 32   |
|----------------|------|------|------|------|------|------|
| Polzahl        | 3    | 4    | 5    | 3    | 4    | 5    |
| a              | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| b              | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| c              | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 |
| d              | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 |
| e ø            | 5,5  | 5,5  | 5,5  | 5,5  | 5,5  | 5,5  |
| f              | 8,0  | 8,0  | 8,0  | 8,0  | 8,0  | 8,0  |
| h              | 46,0 | 46,0 | 46,0 | 55,0 | 55,0 | 55,0 |
| i              | 50,0 | 51,0 | 54,0 | 60,0 | 60,0 | 60,0 |
| l ø            | 57,0 | 65,0 | 70,0 | 78,0 | 78,0 | 78,0 |
| α              | 20°  | 20 ° | 20°  | 20°  | 20°  | 20°  |
| Leiter mm² min | 1,5  | 1,5  | 1,5  | 2,5  | 2,5  | 2,5  |
| Leiter mm² max | 4    | 4    | 4    | 10   | 10   | 10   |
|                |      |      |      |      |      |      |