




# RED<sup>®</sup>

ÜBERZEUGT. EINFACH.

Schlag-/Nageldübel flacher Kragen,  
Polyamid, Zylinderkopf, Kreuzschlitz



4 046725 359319

## Leistungsmerkmale

Der RED Schlag-/Nageldübel ist eine perfekte Kombination aus Funktionalität und einer sehr guten Qualität. Durch die präzise Führung des Nagels kann man den Schlag-/Nageldübel einfach einschlagen. Der Dübel ist aus Nylon und somit reißfest sowie Hitze- und Kältebeständig.

Der verzinkte Nagel sichert eine hohe Korrosionsbeständigkeit.

Der Schlag-/Nageldübel besitzt einen schlaggeschützten Kreuzschlitz und schützt somit vor einer Beschädigung des Antriebes. Die Einschlagsicherung verhindert ein vorzeitiges Spreizen.

Material Dübel: Polyamid PA 6

Material Nagel: Stahl

Zugfestigkeit 500-700 N/mm<sup>2</sup>.

Die Oberfläche des Nagels ist galvanisch verzinkt.

## Kennzeichnung



## Merkmale

|         |              | Bohrlochdurchmesser | Befestigungsstärke | Länge |
|---------|--------------|---------------------|--------------------|-------|
| 5836488 | 2110-20-0003 | 5 mm                | 25 mm              | 35 mm |
| 5836489 | 2110-20-0004 | 6 mm                | 30 mm              | 40 mm |
| 5836490 | 2110-20-0005 | 6 mm                | 30 mm              | 55 mm |
| 5836491 | 2110-20-0006 | 6 mm                | 30 mm              | 80 mm |

## Bestelldaten

| DEHA-Nr. | Type            | Artikel      | EAN           | Farbe | VPE      |
|----------|-----------------|--------------|---------------|-------|----------|
| 5836488  | BFM-SND FK 5x35 | 2110-20-0003 | 4046725359319 | natur | 200 Stk. |
| 5836489  | BFM-SND FK 6x40 | 2110-20-0004 | 4046725359326 | natur | 200 Stk. |
| 5836490  | BFM-SND FK 6x55 | 2110-20-0005 | 4046725359333 | natur | 200 Stk. |
| 5836491  | BFM-SND FK 6x80 | 2110-20-0006 | 4046725359340 | natur | 100 Stk. |


## Specifications



# RED<sup>®</sup>

SIMPLY. CONVINCING.

Knock-in anchor; polyamide, cylinder head, phillips head



Application

Ordering data

### Performance features

The knock-in anchor is a perfect combination of functionality and very good quality. The knock-in anchor is made of nylon and thus tear resistant, heat and cold resistant.

The galvanized nail ensures high resistance against corrosion.

The knock-in anchor has a shock-proof phillips head.

Material anchor: polyamide

Material nail: steel

Tensile strength: The surface of the nail is galvanized

### Labels



## General Data

|         |              | borehole diameter | fastening Strength | Length |
|---------|--------------|-------------------|--------------------|--------|
| 5836488 | 2110-20-0003 | 5 mm              | 25 mm              | 35 mm  |
| 5836489 | 2110-20-0004 | 6 mm              | 30 mm              | 40 mm  |
| 5836490 | 2110-20-0005 | 6 mm              | 30 mm              | 55 mm  |
| 5836491 | 2110-20-0006 | 6 mm              | 30 mm              | 80 mm  |

## Order data

| DEHA-Nr. | Type            | item-number  | EAN number    | color | VE       |
|----------|-----------------|--------------|---------------|-------|----------|
| 5836488  | BFM-SND FK 5x35 | 2110-20-0003 | 4046725359319 | natur | 200 pcs. |
| 5836489  | BFM-SND FK 6x40 | 2110-20-0004 | 4046725359326 | natur | 200 pcs. |
| 5836490  | BFM-SND FK 6x55 | 2110-20-0005 | 4046725359333 | natur | 200 pcs. |
| 5836491  | BFM-SND FK 6x80 | 2110-20-0006 | 4046725359340 | natur | 100 pcs. |

Subject to change w/o notice.

Verpackungsregisternr. DE3513737456573; WEEE-Reg.-Nr. DE 89717721

DEHA Elektrohandels-gesellschaft mbH & Co.KG, Weilimdorfer Str. 74/2, 70839 Gerlingen, Germany

www.deha.de

2

GB