


LED surface mounted downlight
Artikel-Nr. 12074183



LED surface mounted downlight, black, round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 15W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.125lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: Yes, Control: on/off.

Artikel-Nr.	12074183
Stand:	07.12.2021 10:15

Colour temperature	3000 K
Colour	Black
Length	100 mm
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Power	15 W
Lamp	LED
scope of delivery	Incl. converter for connection to the 230-V mains voltage

Colour rendering	CRI > 80
Control	on/off
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Adjustability	Not adjustable
Length	100 mm
Width	100 mm
Aufbauhöhe	100 mm
Circuit type	Parallel conduction