


LED recessed downlight incl. optional surface-mounting housing
Artikel-Nr. 12078073



LED recessed downlight incl. optional surface-mounting housing, white, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp optimized for installation in furniture and wood-based materials. This lamp can be used as a recessed (hole cut-out: 54 mm, installation depth: 16 mm) as well as a surface-mounted lamp (screw distance: 42 mm). . Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 3.3W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 195lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 92°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12078073
Stand:	25.10.2021 20:19

Colour temperature	3000 K
Colour	White
Beam angle	92 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Lamp holder	Plug&Play
Power	3,3 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Outer diameter	65 mm
Built-in diameter	54 mm
Installation depth	16 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Aufbauhöhe	17 mm
Circuit type	Series conduction