

Han-Yellock 30M carrier hood button slot



Part number	11 13 300 0110	
Specification	Han-Yellock 30M carrier hood button slot	
HARTING eCatalogue	https://b2b.harting.com/11133000110	
Identification		
Category	Hoods/Housings	
Series of hoods/housingsHan-Yellock®		
Type of hood/housing	Carrier hood	
Description of hood/ housing	Push button, slot	

Version

Locking type	Push button
Size	Han-Yellock [®] 30
Field of application	Hoods/housings for outdoor applications

Technical characteristics

Limiting temperature	-40 +125 °C
Un-/locking temperature	-10 +85 °C
Mating cycles	≥500
Degree of protection and to IEC 60520	IP65
Degree of protection acc. to IEC 60529	IP67

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Passivated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Polyamide Stainless steel
Colour (locking)	Melon yellow
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties	
REACH ANNEX XIV substances	No
REACH SVHC substances	No
Specifications and approvals	
Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
Commercial data	
Commercial data Packaging size	1
	1 217.8 g
Packaging size	