


LED power supply 24 V DC, dimmable

Article no. 17231000







Tende

LED power supply unit 24 V DC, dimmable, white, rectangular. Material: Plastic, Protection rating on room side: to DIN EN 60529: IP20, Protection class: (EN 61140) II, Voltage: 24 V DC, Power: 75 W, Dimmable: Yes, Type of dimming: Trailing edge phase control.

Article data	
Article no.	17231000
GTIN	4251433938453
Short description	LED power supply 24 V DC, dimmable
Material	Plastic
Colour	White
Shape	Rectangular
Length	185 mm
Width	60 mm
Hight	31 mm
Weight	0.480 kg
stamp	ENEC, MM
Conformance	CE



LED power supply 24 V DC, dimmable

Article no. 17231000

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
Protection class	II.
Degree of protection	IP20
Power min	12 W
Power max.	75 W
Output_ripple_current	300
Starting current	30 A, 300 μs
Suitable for emergency lighting	No
measure point (tc)	0° C
Power factor	0.95
max. no. lights on B10 A	9
max. no. lights on B16 A	14
Output voltage max	24.00 V
Output voltage min.	24.00 V
Control	Trailing-edge phase
Connection type-primary	Screw-in connection
Connection type-secondary	Screwed terminal
Number of poles	3
Enviroment temprature (ta)	-10 °C bis +45 °C
Average nominal lifespan	30000 h
Output current	3,1 A mA

Packing data	
Gross weight	0.5 kg
Length of packaging	65 mm
Packaging width	35 mm
Packaging hight	185 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.