


LED system recessed spot COUPLED, dim2warm

**Artikel-Nr. 12634073**

LED system recessed spot COUPLED, dim2warm, white, round. In a compact design, for installation in tool-less rapid assembly systems. If the lamp is dimmed, the color temperature is reduced. Installation is only with plaster or installation frame 82030170 or 82032170 possible. . Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 500 mA, Power: 9.4W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 920lm, Colour temperature: from 1.800 K up to 3.000 K, Beam angle: 34°, Adjustability: Rotable and pivoted, With control gear: No, Control: Dimming depending on driver.

<b>Artikel-Nr.</b>	<b>12634073</b>		
<b>Stand:</b>	26.10.2021 01:58		
Colour temperature	3000 K - 1800 K	Installation depth	94 mm
Colour	White	Current	500 mA
Beam angle	34 °	Luminous flux	920 lm
Amount of light sources / fittings	1 Qty	Degree of protection	IP20
Material	Aluminium / Plastic	Protection class	III
Power	9,4 W	Adjustability	Rotable and pivoted
Lamp	LED	Rotation angle	350 °
Colour rendering	CRI > 90	Swivel angle	20 °
Control	Dimming depending on driver	Circuit type	Series conduction
Outer diameter	68 mm		