


LED recessed spot

Artikel-Nr. 34261073

recessed spot, weiß, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 710lm, Colour temperature: 2700 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, control: Trailing-edge phase. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr. 34261073
Stand: 20.07.2021 19:48

Colour of light	2700 K
Colour	White
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
control	Trailing-edge phase

Outer diameter	82 mm
Built-in diameter	68 mm
Installation depth	38 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Pivoted
Swivel angle	30 °
Circuit type	Parallel conduction