



profiled light with adjustable pull pendants

Product-Nr.	150814-05
EAN:	4260556625799
Model:	PROFILED Zugpendel
Order number:	150814-05
Model:	PROFILED Zugpendel
Type:	profiled light with adjustable pull pendants
Illuminant:	SMD LED
Total output incl. driver:	~34 W
Power consumption:	~30 W
Lamp luminous flux:	4676 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	90-305V AC $\pm$ 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	1 pair of adjustable pull pendants, 1x 90-305V ceiling transferpoint via open cable ends
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C -> +45 °C (14 °F -> 113 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
Length [A]:	1200 mm (~47,24")
Weight (net):	3200 g (~113 oz)
Gross weight:	3850 g (~136 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	no
Mounting accessories:	optional
Made in:	Germany

