

profiled light with t-slot backsided



Product-Nr.	150314-01
EAN:	4260556623771
Model:	PROFILED DC
Order number:	150314-01
Model:	PROFILED DC
Type:	profiled light with t-slot backsided
Illuminant:	SMD LED
Power consumption:	~11 W
Lamp luminous flux:	1670 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP40
Class of protection:	III
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C -> +60 °C (14 °F -> 140 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 100.000h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
Length [A]:	500 mm (~19,69")
Weight (net):	850 g (~30 oz)
Gross weight:	1300 g (~46 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	optional via accessories
Mounting accessories:	optional
Made in:	Germany
Feature:	universally accepted as workbench lighting, system light or

