



## Distribution box M12-A, 4-way, with fixed cable



|                                     |                                                                                     |
|-------------------------------------|-------------------------------------------------------------------------------------|
| <b>Product-Nr.</b>                  | 200300-01                                                                           |
| <b>EAN:</b>                         | 4260556622019                                                                       |
| <b>Model:</b>                       | Zubehör Anschluss                                                                   |
| <b>Order number:</b>                | 200300-01                                                                           |
| <b>Model:</b>                       | Zubehör Anschluss                                                                   |
| <b>Type:</b>                        | Distribution box M12-A, 4-way, with fixed cable                                     |
| <b>Coding:</b>                      | A-coded                                                                             |
| <b>Amount:</b>                      | 1 piece                                                                             |
| <b>Suitable for:</b>                | LED2WORK lights 24V DC, except for RGB and RGB-W luminaires                         |
| <b>Cable length:</b>                | 10 m (~32,81 ft.)                                                                   |
| <b>Attachment to a luminaire:</b>   | Connector socket M12                                                                |
| <b>Number of poles:</b>             | 4                                                                                   |
| <b>Material:</b>                    | Contact carrier: plastic, PA, BK; Seal: FPM/FKM; Contacts: metal, CuSn, gold-plated |
| <b>Current load per PIN:</b>        | 2000 mA                                                                             |
| <b>Ambient temperature:</b>         | -30°C -> +90 °C (-22 °F -> 194 °F)                                                  |
| <b>Passage resistance (ohms):</b>   | < 0,005                                                                             |
| <b>Insulation resistance (Ohm):</b> | >= 100 Mio.                                                                         |
| <b>Protection class (mounting):</b> | IP65, IP67                                                                          |
| <b>Cable material:</b>              | PUR                                                                                 |
| <b>Contact carrier material:</b>    | Plastic, PA, BK                                                                     |
| <b>Sealing material:</b>            | FPM/FKM                                                                             |
| <b>Contact material:</b>            | Metal, CuSn, gold-plated                                                            |
| <b>Standards:</b>                   | IEC 61076-2-101                                                                     |
| <b>Dimensions (mm):</b>             | 115,4 mm x 54 mm x 25,5 mm (~4,54" x ~2,13" x ~1")                                  |
| <b>Weight (net):</b>                | 500 g (~18 oz)                                                                      |
| <b>Gross weight:</b>                | 550 g (~19 oz)                                                                      |
| <b>Note:</b>                        | Mechanical life: > 100 mating cycles                                                |