



#### Product Features

1.2GB WIFI access point PoE, flush-mounted, with RJ45 front port, pure white (similar to RAL 9010)

- front RJ45 port for A data terminal
- mounting in conventional 2-gang installation pots (installation depth 51 mm)
- nominal operating voltage: PoE (Class 2)
- power consumption: 5,5 VA typ.
- temperature range: -5°C - 35° C
- RJ45 - opening at the frontside for one data equipment
- indication of functions at illuminated RJ45 -outlet
- connection of data cable and power supply via detachable screw terminals on the frontside
- transmission rate data cable: 1000 Mbit/s
- transmission rate RJ45: 100Mbit/s
- radio standards: IEEE 802.11 b/g/n/ac (Wave 2)
- frequency/data rate: 2,4 GHz / 5 GHz, 300 Mbit/s / 876 Mbit/s (Dualmode)
- safety and encryption: WPA, WPA2, MAC-Filter
- with timer and time-switching function
- guest WiFi additional
- central management
- reset via reset-magnet or reset-contact
- suitable for the UAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

#### Features

General	
Surface	high-gloss
Support ring	Yes
Design capability	Yes
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85415900
Country of manufacture	DE
GTIN (EAN)	4043921665800
ETIM class	STANDARD
Mounting types	
flush-mounted, 2-gang Box	Yes

Dimensions/Weights without packaging	
Length mm	141
Width mm	70
Height mm	57,5
Net weight piece kg	0,139
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,31
Packaging unit Width mm	145
Packaging unit Height mm	95
Packaging unit Depth mm	185
References	
Accessories	10000042, 10000062, 13500042, 13500062, 13910043, 13910063, 39200010
Similar article	226104031, 226104032, 226104062

