

wall mounting socket outlet, switched, interlocked,  
 chemically resistant - housing dimensions 170x90



| Product description       |                                                       |
|---------------------------|-------------------------------------------------------|
| BALS-Prd.-Nr              | 16916                                                 |
| EAN                       | 4024941169165                                         |
| Product category          | TE wall mounting socket outlet, switched, interlocked |
| Current                   | 16A                                                   |
| Number of poles           | 5p                                                    |
| Arrangement of phases     | 3p+N+PE                                               |
| Position of earth contact | 6 h                                                   |
| Voltage                   | 200/346 - 240/415V~                                   |

| Product description    |                                                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Frequency              | 50/60Hz                                                                                                                      |
| Protection degree      | IP67                                                                                                                         |
| Colour code            | red RAL 3000                                                                                                                 |
| Colour of appliance    | Hinged lid red RAL 3000, Bayonet ring lightbeige, Housing bottom lightbeige, Housing top lightbeige, Control knob lightbeige |
| Connection design      | screwless spring terminals with Kontex-Kontakt                                                                               |
| Maximum conductor size | 4,0 qmm                                                                                                                      |
| Cable entry            | top entry M20 bottom entry M25/20                                                                                            |
| Height                 | 195mm                                                                                                                        |
| Width                  | 90mm                                                                                                                         |
| Depth                  | 123mm                                                                                                                        |
| Dimension of enclosure | 170x90 mm (HxW)                                                                                                              |
| Material of enclosure  | Polycarbonate+Polyester light - beige                                                                                        |
| Contacts               | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated                     |

| Additional technical properties |                                                                                                             |
|---------------------------------|-------------------------------------------------------------------------------------------------------------|
|                                 | The cable entry is one at top open and two at bottom closed                                                 |
|                                 | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm, Lower part of housing rotatable by 180° |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.69 kg / Piece |
| Packaging      | Carton          |
| Content amount | 1 ST            |
| EAN            | 4024941169165   |
| Length         | 124 mm          |
| Width          | 91 mm           |
| Height         | 196 mm          |
| Weight         | 0.75 kg         |
| Volume         | 2,211.664 ccm   |

