# **Installation Equipment and Accessories**

## Reducer



## CMP-737-D-M3-M2-4 Art. No. 252980



- · Ex d and Ex e metal reducers
- Large selection of thread types and sizes
- Operating temperature range: -60 C° ... +200 °C
- · Worldwide certification, IECEx, ATEX, UL and cCSAus

## WebCode 737DA



The metal Ex-d reducers from the 737 series enable adaptation of the thread sizes and types. There is a wide selection of different versions available. They have worldwide certification according to IECEx, ATEX, UL and cCSAus.

#### **Technical Data**

Explosion Protection	
Application range (zones)	1 2
	20
	21 22
IFOE was sortificate	<del></del>
IECEx gas certificate	IECEX CML 18.0177X
IECEx gas explosion protection	Ex e IIC Gb
IECEx firedamp certificate	IECEx CML 18.0177X
IECEx firedamp protection	Ex db I Mb
IECEx firedamp protection	Ex eb I Mb
ATEX gas certificate	CML 18ATEX1320X
ATEX gas explosion protection	
ATEX firedamp certificate	CML 18ATEX1320X
ATEX firedamp protection	□ I M2 Ex db I Mb
ATEX firedamp protection	© IM2 ebIMb
CSA gas certificate	CSA 1055233
EAC certificate	TS RU S-GB.AA87.B.00487
EAC gas explosion protection	🗓 1 Ex d e IIC Gb X
EAC dust explosion protection	🛭 Ex ta IIIC Da X
Note	The product certification and certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)
Ambient Conditions	
Ambient temperature	-60 °C +200 °C
Mechanical Data	
Version	Metric / metric
Degree of protection (IP)	IP66
Degree of protection note	IP67 and IP68 mounting in accordance with the specifications of the manufacturer, CMP

## **Installation Equipment and Accessories**






## CMP-737-D-M3-M2-4 Art. No. 252980

Mechanical Data	
Material	Stainless steel
Silicone-free	Yes
Width across corners	33 mm
Width across flats	30 mm
External thread	M25
Thread size	M25
Thread length	15 mm
Thread pitch	1,5
Thread pitch 2	1,5
Internal thread	M20
Impact strength (IEC 62262)	IK10
Packaging unit	1
Weight	0.075 kg
Weight	0.17 lb

#### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



O = External thread

I = Internal thread

SW = Width across flats

E = Width across corners

B = Length

L = Thread length

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.