





LED recessed spot set, dim2warm, dimmable
Artikel-Nr. 39462253



LED recessed spot set, dim2warm, dimmable, alu, square. In a compact design, for installation in tool-less rapid assembly systems. If the lamp is dimmed, the color temperature is reduced. Set including a converter for 230-V mains voltage, trailing-edge phase, dimensions of converter: L 110 x W 50 x H 19 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 460lm, Colour temperature: from 1.800 K up to 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, Control: Trailing-edge phase.

Artikel-Nr.	39462253
Stand:	25.10.2021 22:20

Colour temperature	3000 K - 1800 K
Colour	Alu
Length	82 mm
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	6 W
Lamp	LED
Colour rendering	CRI > 80
Control	Trailing-edge phase

Built-in diameter	68 mm
Installation depth	38 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Pivoted
Length	82 mm
Width	82 mm
Swivel angle	30 °
Circuit type	Parallel conduction