

7570/12-407 Art. No. 126371



- Degree of protection IP66, suitable for use in Zones 2 and 22 worldwide, extreme temperature range of -60 to $+55$ °C
- With AC-3 motor switching capacity according to IEC/EN 60947-3
- No impact of torsional forces from the cable on the seal

WebCode 7570C



R. STAHL Series 7570/12 SolConeX plugs for Zone 2/22 are silicone-free 3-, 4- or 5-pole 16 A plugs. The floating pins allow them to be inserted and removed quickly and easily. The pivoting strain relief makes it easier to install the cable. Self-cleaning and corrosion-free plug pins made from high-quality materials ensure optimum electrical contact.

Technical Data

Explosion Protection

Application range (zones)	2 22
---------------------------	---------

Electrical Data

Mechanical service life	> 5x10 ³ plug cycles
Type of voltage	Low voltage
Frequency range	50 / 60 Hz

Ambient Conditions

Ambient temperature	-30 °C ... $+55$ °C (T80 °C) (T80 °C)
Ambient temperature	-86 °F ... $+131$ °F (T80 °C) (T80 °C)

Mechanical Data

Schutzart IP (IEC 60079)	IP66
Enclosure material	Polyamide, Glass fibre reinforced
Silicone-free	Yes
Finely stranded connection cross section	1.5 – 4 mm ²
Connection cross-section AWG finely stranded	AWG 16 - AWG 12
Width	89 mm
Width, inches	3.5 in
Height	89 mm
Height, inches	3.5 in
Length	176 mm
Length, inches	6.93 in
Impact strength (IEC 60079)	7 J
Impact strength (IEC 62262)	IK10
Colour code	Black
Coding (clock hour position)	7
Series	SolConeX

7570/12-407 Art. No. 126371

Mechanical Data

Detailed number of poles	3 P + PE
Weight	0.38 kg
Weight	0.84 lb


Mounting / Installation

Connection	Screw terminal
------------	----------------

Components

Cable diameter	8 ... 18 mm
----------------	-------------

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



2 P + PE: A = 43.5 mm B = 76 mm

3 P + PE: A = 49 mm B = 89 mm

3 P + N + PE: A = 56.5 mm B = 92 mm

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.