

Datenblatt Art. BM0024725

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

CONFERENCE Steckdoseneinheit

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung		Supply cable	
Stecker	Installationssteckverbinder	Plug	Building installation connector
Ableitung		Through cable	
Kupplung	Installationssteckverbinder	Coupling	Building installation connector
2-polig mit Schutzkontakt Schwarz, ähnlich RAL 9005 20A 250V~, IP20		2-pole with earthing contact Black, similar to RAL 9005 20A 250V~, IP20	
Stromausgang		Power output	
Steckdosen		Socket outlets	
1x CEE 7/3 (Type F)		1x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz Schwarz, ähnlich RAL 9005, 35° 16 A / 250 V~, IP20		2-pole with earthing contact With shutter Black, similar to RAL 9005, 35° 16 A / 250 V~, IP20	
Funktionsmodule		Function modules	
USB-C Charger 100.0 W (85 mm)		USB-C Charger 100.0 W (85 mm)	
Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C1 oder C2 (Single Mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 3.0 A 27.0 W DC 12.0 V 3.0 A 36.0 W DC 15.0 V 3.0 A 45.0 W DC 20.0 V 5.0 A 100.0 W DC PPS: 3.3 V-21.0 V 5.0 A (max. 105 W)	Output voltage / Output current / Output power C-port C1 or C2 port (single mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 3.0 A 27.0 W DC 12.0 V 3.0 A 36.0 W DC 15.0 V 3.0 A 45.0 W DC 20.0 V 5.0 A 100.0 W DC PPS: 3.3 V-21.0 V 5.0 A (max. 105 W)

Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C1-port (Beide Ausgänge/Dual Mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 3.0 A 27.0 W DC 12.0 V 3.0 A 36.0 W DC 15.0 V 3.0 A 45.0 W DC 20.0 V 3.25 A 65.0 W DC PPS: 3.3 V-21.0 V 3.0 A (max. 63.0 W)	Output voltage / Output current / Output power C1-port (both output/dual mode)	DC 5.0 V 3.0 A 15.0 W DC 9.0 V 3.0 A 27.0 W DC 12.0 V 3.0 A 36.0 W DC 15.0 V 3.0 A 45.0 W DC 20.0 V 3.25 A 65.0 W DC PPS: 3.3 V-21.0 V 3.0 A (max. 63.0 W)
--	---	---	---

Ausgangsspannung / Ausgangsstrom / Ausgangsleistung C2-port (Beide Ausgänge/Dual Mode)	DC 5.0 V 3.0 A 15 W DC 9.0 V 3.0 A 27.0 W DC 12.0 V 2.5 A 30.0 W DC 15.0 V 2.0 A 30.0 W DC 20.0 V 1.5 A 30.0 W DC PPS: 3.3 V-11.0 V 3.0 A (max. 33.0 W)	Output voltage / Output current / Output power C2-port (both output/dual mode)	DC 5.0 V 3.0 A 15 W DC 9.0 V 3.0 A 27.0 W DC 12.0 V 2.5 A 30.0 W DC 15.0 V 2.0 A 30.0 W DC 20.0 V 1.5 A 30.0 W DC PPS: 3.3 V-11.0 V 3.0 A (max. 33.0 W)
--	---	---	---

Durchschnittseffizienz		Average active efficiency	
DC 5.0 V 3.0 A 15.0 W	83.0 %	DC 5.0 V 3.0 A 15.0 W	83.0 %
DC 9.0 V 3.0 A 27.0 W	88.0 %	DC 9.0 V 3.0 A 27.0 W	88.0 %
DC 12.0 V 3.0 A 36.0 W	88.0 %	DC 12.0 V 3.0 A 36.0 W	
DC 15.0 V 3.0 A 45.0 W	88.0 %	DC 15.0 V 3.0 A 45.0 W	88.0 %
DC 20.0 V 5.0 A 100 W	89.0 %	DC 20.0 V 5.0 A 100 W	89.0 %
DC PPS: 3.3 V-21.0 V 5.0A (max. 105.0 W)	91.0 %	DC PPS: 3.3 V-21.0 V 5.0A (max. 105.0 W)	91.0 %

Effizienz bei niedriger Last (10 %)		Efficiency at low load (10 %)	
DC 5.0 V 3.0 A 15.0 W	30.0 %	DC 5.0 V 3.0 A 15.0 W	30.0 %
DC 9.0 V 3.0 A 27.0 W	80.0 %	DC 9.0 V 3.0 A 27.0 W	80.0 %
DC 12.0 V 3.0 A 36.0 W	81.0 %	DC 12.0 V 3.0 A 36.0 W	81.0 %
DC 15.0 V 3.0 A 45.0 W	78.0 %	DC 15.0 V 3.0 A 45.0 W	78.0 %
DC 20.0 V 5.0 A 100 W	83.0 %	DC 20.0 V 5.0 A 100 W	83.0 %
DC PPS: 3.3 V-21.0 V 5.0A (max. 105.0 W)	84.0 %	DC PPS: 3.3 V-21.0 V 5.0A (max. 105.0 W)	84.0 %

Leistungsaufnahme bei Nulllast	0.24 W	No-load power consumption	0.24 W
--------------------------------	--------	---------------------------	--------

Ladestandard Power Delivery	USB 3.1 PD	Charging standards Power Delivery	USB 3.1 PD
--------------------------------	------------	--------------------------------------	------------

Weitere Produkteigenschaften

Further product attributes

Plattform	Standard (kHE)	Plattform	Standard (kHE)
Material Gehäuse: Aluminium eloxiert		Material Housing: Aluminium anodised	
Abdeckung: PA6 GF30 850°C, schwarz ähnlich RAL 9005		Cover: PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	

1x CONFERENCE Steckdoseneinheit

1x CONFERENCE power strip

Im Karton

In carton

Optionales Zubehör

1x CONFERENCE Rahmen

Optional accessories

1x CONFERENCE frame

Umgebungsbedingungen

Environmental conditions

Maximale Höhe 0 - 2000m
Umgebungstemperatur bei Montage und Nutzung 5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.
Umgebungstemperatur bei Transport und Lagerung -25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend) 5 – 95%
Schutzart IP20

Maximum height 0 - 2000m
Surrounding temperature during mounting and use 5°C – 35°C
Protect from direct sunlight.
Surrounding temperature during transport and storage -25°C - 60°C
Relative humidity (non-condensing) 5 – 95%
Protection type IP20

Konformität

Conformity

Angewandte Normen IEC 62368-1 (USB-Charger)
 EN 62368-1 (USB-Charger)

Applied standards IEC 62368-1 (USB-Charger)
 EN 62368-1 (USB-Charger)