


connector low voltage - with cable gland, Multi-Grip



Product description	
BALS-Prd.-Nr	4538
EAN	4024941045384
Product category	ELV connector
Current	32A
Number of poles	2p
Arrangement of phases	2P
Position of earth contact	10 h
Frequency	DC
Protection degree	IP44

Product description	
Colour code	grey RAL 7035
Colour of appliance	Hinged lid grey RAL 7035, Collar grey RAL 7035, Housing cover grey RAL 7035, Cable gland grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	10,0 qmm
Cable entry	with cable gland
Height	152mm
Width	62mm
Depth	67mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter up to max. 23.0 mm, For cable diameter from 11 up to max. 23,5 mm, Multi-Grip cable gland with gasket and integrated strain relief

Logistics data	
Weight/pcs	0.183 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941045384
Length	67 mm

Logistics data	
Width	62 mm
Height	152 mm
Weight	0.184 kg
Volume	631.408 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941837712
Length	275 mm
Width	175 mm
Height	137 mm
Weight	1.955 kg
Volume	5,737.5 ccm

Ampere Polzahl	16 2	16 3	32 2	32 3
a	62,0	62,0	62,0	62,0
b	96,0	96,0	96,0	96,0
c	152,0	152,0	152,0	152,0
d	67,0	67,0	67,0	67,0
e ø	24,5	24,5	24,5	24,5
Leiter mm² min	4	4	4	4
Leiter mm² max	10	10	10	10

16 MB 44