

Han 10HPR Base panel 1x M32 screw lock



| Part number | 19 40 010 1262 |
|--------------------|--|
| Specification | Han 10HPR Base panel 1x M32 screw lock |
| HARTING eCatalogue | https://b2b.harting.com/19400101262 |
| | |

Identification

| Category | Hoods/Housings |
|-----------------------------------|-------------------------|
| Series of hoods/housings Han® HPR | |
| Type of hood/housing | Surface mounted housing |

Version

| Locking type | Screw locking |
|----------------------|---|
| Size | 10 B |
| Version | Side entry |
| Cable entry | 1x M32 |
| Field of application | Hoods/housings for harsh outdoor environments |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|--|
| Tightening torque (screw locking) | 4 Nm |
| Degree of protection acc. to IEC 60529 | IP65 IP68 IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast Corrosion resistant |
|-------------------------|--|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| Material (locking) | Stainless steel |
| RoHS | compliant |
| ELV status | compliant |



Material properties

| China RoHS | e |
|-----------------------------|----|
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| Approvals | DNV GL |
|-----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E235076 |
| | CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|----------|
| Net weight | 899.8 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |