

# Han 48HPR cover angled housing 5xM32



Part number	19 40 048 9812
Specification	Han 48HPR cover angled housing 5xM32
HARTING eCatalogue	https://b2b.harting.com/19400489812
Identification	
Category	Hoods/Housings
Series of hoods/housings Han <sup>®</sup> HPR	
	JSHan <sup>®</sup> HPR
Type of hood/housing	ISHan <sup>®</sup> HPR Mounting cover

#### Version

Locking type	Screw locking
Size	48 B
Cable entry	5x M32
Field of application	Hoods/housings for harsh outdoor environments
Pack contents	4 distance pieces
	4x M6 screw
	4 washers

## **Technical characteristics**

Limiting temperature	-40 +125 °C
Tightening torque (screw locking)	4 Nm
Degree of protection acc. to IEC 60529	IP65
	IP68
	IP69 / IPX9K acc. to ISO 20653

### Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Stainless steel
RoHS	compliant

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



### Material properties

China RoHS e   REACH Annex XVII substances No   REACH ANNEX XIV substances No	ELV status	compliant
REACH ANNEX XIV substances No	China RoHS	e
	REACH Annex XVII substances	No
	REACH ANNEX XIV substances	No
REACH SVHC substances No	REACH SVHC substances	No

### Specifications and approvals

Approvals	DNV GL
Commercial data	
Packaging size	1
Net weight	679 g
Country of origin	Germany
European customs tariff number	85389099