

## Han 10HPR Hood Side M25 Screw lock



|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 40 010 0511                                                                        |
| Specification      | Han 10HPR Hood Side M25 Screw lock                                                    |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19400100511">https://b2b.harting.com/19400100511</a> |

### Identification

|                          |                      |
|--------------------------|----------------------|
| Category                 | Hoods/Housings       |
| Series of hoods/housings | Han <sup>®</sup> HPR |
| Type of hood/housing     | Hoods                |

### Version

|                      |                                               |
|----------------------|-----------------------------------------------|
| Locking type         | Screw locking                                 |
| Size                 | 10 B                                          |
| Version              | Side entry                                    |
| Cable entry          | 1x M25                                        |
| Field of application | Hoods/housings for harsh outdoor environments |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                |
| Tightening torque (screw locking)      | 4 Nm                                           |
| Degree of protection acc. to IEC 60529 | IP65<br>IP68<br>IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                  |

### Material properties

|                             |                                           |
|-----------------------------|-------------------------------------------|
| Material (hood/housing)     | Aluminium die-cast<br>Corrosion resistant |
| Surface (hood/housing)      | Powder-coated                             |
| Colour (hood/housing)       | RAL 9005 (jet black)                      |
| Material (locking)          | Stainless steel                           |
| RoHS                        | compliant                                 |
| ELV status                  | compliant                                 |
| China RoHS                  | e                                         |
| REACH Annex XVII substances | No                                        |



Pushing Performance

## Material properties

|                            |    |
|----------------------------|----|
| REACH ANNEX XIV substances | No |
| REACH SVHC substances      | No |

## Specifications and approvals

|           |                                                            |
|-----------|------------------------------------------------------------|
| Approvals | DNV GL                                                     |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |

## Commercial data

|                                |          |
|--------------------------------|----------|
| Packaging size                 | 1        |
| Net weight                     | 490 g    |
| Country of origin              | Germany  |
| European customs tariff number | 85389099 |