

## Han® C Push-In module, female 1.5-6mm<sup>2</sup>



Image is for illustration purposes only. Please refer to product description.

Part number	09 14 003 5101
Specification	Han® C Push-In module, female 1.5-6mm <sup>2</sup>
HARTING eCatalogue	<a href="https://harting.com/09140035101">https://harting.com/09140035101</a>

### Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® C module
Size of the module	Single module

### Version

Termination method	Push-In
Gender	Female
Number of contacts	3

### Technical characteristics

Conductor cross-section	1.5 ... 6 mm <sup>2</sup>
Wire outer diameter	≤7.4 mm
Rated current	40 A
Rated voltage	690 V
Rated impulse voltage	8 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Stripping length	12 mm
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500



Pushing Performance  
Since 1945

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

## Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984
	IEC 61373 Category 2
	IEC 60352-7

## Commercial data

Packaging size	2
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140501492
eCl@ss	27440217 Module for industrial connectors (power/signals)
ETIM	EC000438
UNSPSC 24.0	39121552