

11.02.8561 Art. No. 149234



- Easy to maintain due to use of standard DIAZED fuses
- Practical: Defective fuses easy to see from the outside
- For rated operational voltages up to 500 V and rated operational currents up to 63 A

WebCode **8561B**



R. STAHL Series 8561/02 fuse elements primarily protect the consumer outputs in Ex e distribution fuse boards or offer back-up protection for the system. Since they are equipped with standard DIAZED system fuses, they are extremely easy to maintain and defective fuses are easy to see from the outside. They are designed for rated operational voltages up to 500 V and rated operational currents up to 63 A.

Technical Data

Explosion Protection

Application range (zones)	1 2
IECEX gas certificate	IECEX PTB 06.0063U
IECEX gas explosion protection	Ex de IIC T..
ATEX gas certificate	PTB 02 ATEX 1028 U
ATEX gas explosion protection	Ex II 2 G Ex de IIC T..
Certificates	ATEX (PTB), Brazil (ULB), IECEX (PTB)

Electrical Data

Rated operational voltage DC	550 V
Rated operational voltage AC	550 V
Rated operational current	25 A (T..)

Ambient Conditions

Ambient temperature	-20 °C ... +40 °C
---------------------	-------------------

Mechanical Data

Enclosure material	Epoxy resin
Type of fuse link	D II
Weight	0.785 kg
Weight	1.73 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.