LED surface mounted tube luminaire

Product-Nr.	115210-01
EAN:	4260556621685
Model:	INROLED_70 with Borosilicate Glass Protective Tube





Order number:	115210-01
Model:	INROLED_70 with Borosilicate Glass Protective Tube
Type:	LED surface mounted tube luminaire
Illuminant:	SMD LED
Power consumption:	~13 W
Lamp luminous flux:	2004 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Connected load:	24V DC ± 10%
Connection (connector):	Cable entry, internal clamp
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	Microprisms
Beam angle (optics):	125°
Operating temperature:	-10 °C - +45 °C (14 °F - 113 °F)
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium inside
Cover material:	tempered glass, shatterproof
Height [B] x Width [C]:	Ø 70 mm (~2,76“)
Length [A]:	650 mm (~25,59“)
Weight (net):	1450 g (~51 oz)
Gross weight:	2000 g (~71 oz)
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories
Mounting accessories:	Optional
Made in:	Germany
Feature:	cascadable (max. 4.0 A)
cascadable:	yes

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com