## LED system and workplace light

| | |
|---|---|
| **Product-Nr.** | 110994-12 |
| **EAN:** | 4260556623450 |
| **Model:** | UNILED SL RGB-W |




| | |
|---|---|
| Order number: | 110994-12 |
| Model: | UNILED SL RGB-W |
| Type: | LED system and workplace light |
| Illuminant: | RGB SMD + SMD LED |
| Power consumption white: | ~19 W |
| White lamp luminous flux: | 2430 lm |
| Lamp luminous efficiency: | 126 lm/W |
| Power consumption RED: | ~18 W |
| Lamp luminous flux RED: | 480 lm |
| Power consumption GREEN: | ~5 W |
| Lamp luminous flux GREEN: | 710 lm |
| Power consumption BLUE: | ~18 W |
| Lamp luminous flux BLUE: | 300 lm |
| Light distribution: | Direct |
| Light colour white: | 5000K 3-step MacAdam |
| Colour rendering WHITE (Ra): | >80 |
| Connected load: | 24 V DC -10 %+7 % (RGB) – 24 V DC ±10 % (W) |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP50 |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -10 °C - +50 °C (14 °F - 122 °F) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | plastics, soft |
| Height [B] x Width [C]: | 35 mm x 85 mm (~1,38“ x ~3,35“) |
| Length [A]: | 545 mm (~21,46“) |
| Weight (net): | 770 g (~27 oz) |
| Gross weight: | 1320 g (~47 oz) |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Mounting accessories: | Optional |
| Made in: | Germany |
| Feature: | RGB-W: Illumination and beacon in one light |



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com