

wall mounting socket outlet, switched, interlocked - housing dimensions 170x90



Product description	
BALS-Prd.-Nr	160052
EAN	4024941068512
Product category	Wall mounting socket outlet, switched, interlocked
Current	16A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Housing bottom grey RAL 7035, Bayonet ring grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035
Connection design	screwless spring terminals with Kontex-Kontakt
Maximum conductor size	4,0 qmm
Cable entry	top entry M20 bottom entry M25/20
Height	195mm
Width	90mm
Depth	123mm
Dimension of enclosure	170x90 mm (HxW)
Material of enclosure	Polycarbonate
Contacts	the contacts are brass nickel plated, The contact carrier is made of polyamide

Additional technical properties	
	The cable entry is one at top open and two at bottom closed
	In 0-position lockable for 3 padlocks with bow diameter up to 7 mm, Lower part of housing rotatable by 180°

Logistics data	
Weight/pcs	0.637 kg / Piece

Logistics data	
Packaging	Carton
Content amount	1 ST
EAN	4024941068512
Length	124 mm
Width	91 mm
Height	196 mm
Weight	0.697 kg
Volume	2,211.664 ccm

Technical drawing of the 12 MB 6 device. The front view (left) shows a cylindrical body with a central circular feature and a base. Dimensions labeled are 'a' (total height), 'c' (width), 'b' (height to base), and 'd' (height to top of base). The side view (right) shows the profile of the device with a mounting bracket. Dimensions labeled are 'f' (total height), 'g' (height to top of body), 'h' (height to top of base), 'i' (height to top of mounting bracket), 'k' (height to bottom of mounting bracket), and 'e' (height to bottom of body). A 15° angle is indicated for the mounting bracket. The drawing is labeled '12 MB 6' at the bottom left.

Ampere	16	16	16						
Polzahl	3	4	5						
a	90,0	90,0	90,0						
b	170,0	170,0	170,0						
c	77,0	77,0	77,0						
d	137,5	137,5	137,5						
e	108,0	115,0	121,0						
f	191,5	191,5	191,5						
g	6,0	6,0	6,0						
h ø	5,5	5,5	5,5						
i	M20	M20	M20						
k	M20/25	M20/25	M20/25						

12 MB 6