

**Product Features**

- "Splice box, extensible, 19"/1U, 24xLC-D, OM4, erika, grade B"
- sheet steel housing, powder coated
 - with slide-in unit, max. pullout depth ca. 20 cm
 - the box can be offset by 40 mm towards the rear
 - wall mounting possible with separate wall mounting adapter
 - labelled ports
 - individual labelling using label holders
 - front quick release (push-pull)
 - 4 splice cassettes for holding 12 or 24 pigtails
 - inserted crimp splice holder
 - ready to splice with exposed and inserted pigtails incl. 48 x LC-D - ceramic couplings
 - 48 LC-fibre pigtails G50/125 µm, 2 m, MM PC, grade B
 - with test protocol for all fibres incl. serial number
 - mounted blind stops by less than 24 ports
 - 4 x rear screw connection cut-outs (2 x M20/25 each, right/left)
 - 1 x M20 - cable gland in scope of delivery
 - cable bevel entry available as an accessory
 - ETSI mounting adapter available as an accessory
 - wall mount bracket available as an accessory
 - black (similar RAL 9005)

Features

General	
Surface	steel sheet, powder-coated
Labeling field	Yes
Classification	OM4
Protection class IP	20
Halogen Free	Yes
Country of manufacture	DE
GTIN (EAN)	4043921670439
ETIM class	STANDARD
Dimensions/Weights without packaging	
Length mm	483
Width mm	250
Height mm	44
Certifications	
RoHS conform	Yes

Spleissbox 24xLC-D OM4 erika sw

Article no.: 228030124-01

Color: black (similar RAL 9005)

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	2,869
Packaging unit Width mm	510
Packaging unit Height mm	55
Packaging unit Depth mm	380
References	
Accessories	228040002, 228040102, 228040202, 228040302, 228040402, 228060000, 228060100, 228060200, 228060300, 228060400, 228070000, 228070100, 228070200, 228070312
Similar article	228030024, 228030106, 228030112, 228030224, 228030324, 228030624, 228031124