

panel mounting socket outlet, straight - flange 75x75, fixing centers 60x60




Product description	
BALS-Prd.-Nr	130156
EAN	4024941149839
Product category	TE panel mounting socket outlet QUICK-CONNECT, straight
Current	32A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	3 h
Voltage	380V~(50Hz) 440V~(60Hz)

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Enclosure grey RAL 7035, Bayonet ring grey RAL 7035, Hinged lid red RAL 3000
Connection design	screwless spring terminals with Kontex-Kontakt
Maximum conductor size	10,0 qmm
Cable entry	other
Height	99mm
Width	94mm
Depth	119mm
Flange size vertical in mm	75mm
Flange size horizontal in mm	75mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.22 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941149839
Length	119 mm
Width	94 mm
Height	99 mm
Weight	0.221 kg
Volume	1,107.414 ccm
Packaging	Bag
Content amount	1 ST
EAN	4024941149839
Length	119 mm
Width	94 mm
Height	99 mm
Weight	0.221 kg
Volume	1,107.414 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941990936
Length	325 mm
Width	217 mm
Height	210 mm

Logistics data	
Weight	2.406 kg
Volume	13,588.4 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941990936
Length	325 mm
Width	217 mm
Height	210 mm
Weight	2.406 kg
Volume	13,588.4 ccm



4MB503

Ampere Poles	16 3	16 5	32 3	32 4	32 5
a	75,0	75,0	75,0	75,0	75,0
b	75,0	75,0	75,0	75,0	75,0
c	60,0	60,0	60,0	60,0	60,0
d	60,0	60,0	60,0	60,0	60,0
Øe	5,5	5,5	5,5	5,5	5,5
f	7,0	7,0	7,0	7,0	7,0
h	36,0	37,0	46,0	46,0	46,0
i	58,0	59,0	69,0	69,0	69,0
Øl	45,0	55,0	55,0	55,0	65,0
m	4,5	12,0	12,0	12,0	18,5
x	80,0	93,0	97,0	97,0	107,0
y	75,0	86,5	94,0	94,0	101,5
z	94,0	94,0	115,0	115,0	114,0

